


## U-Clamp



- Material: S45C
- Easy adjustment

ORDER NO.	STUD	LxWxH	K.G.	CODE NO.
VCA-404	M12x5"	105x45x35mm	1.5	1015-001
VCA-405	M16x6"	126x54x40mm	2.6	1015-002
VCA-406	M20x7"	155x58x55mm	4.2	1015-003
VCA-408	M24x8"	190x70x65mm	8.2	1015-004

## Pivot Clamp



- The clamping height is adjustable
- With brass plate under the clamp arm for protecting the working material from damage
- By using spherical Flange nut, it will be assured to clamp the material tightly
- The clamping arm is forged
- Material: S45C

ORDER NO.	Table T-Slot Size	Stud X L Size	Body	Clamping height	G.W.	CODE NO.
VCB-404	16	M12x5"	115x42x39	0 or 3 1/2"	1.6	1015-005
VCB-405	20	M16x6"	133x50x49	0 or 4"	2.7	1015-006
VCB-406	22	M20x7"	157x60x54	0 or 4 3/4"	4.6	1015-007
VCB-408	28	M24x8"	7x2 7/8	0 or 6"	8.6	1015-008

## Hand Drift

ORDER NO.VHD-1 CODE NO.1016-001



### An essential tool for machinery processing

Specially applied for: Vertical drill, radial drill, compounding miller, boring miller, and any drill drifting, etc.

- Easy and fast operation.
- Enhance the working efficiency.
- Protect toolings to be safe.
- Economical, practical & durable.

Suit For Spindle Notes	Length	30pcs/Box Size	30pcs/ Carton Size	N.W.(kg)
M.T.#2 #3 #4 #5	375mm	385x45x37mm	390x270x240mm	1.3