






Machine Reamers Carbide Tipped



VERTEX®



Work Material / Velocity m/min

GR.1 Non alloyed steels Alloyed Steels	GR.2 Heat resistant steels Stainless steels	GR.3 Hardened steels < 48 HRC	GR.4 Hardened steels 48-56 HRC	GR.6 Iron	GR.7 Titanium	GR.8 Nickel	GR.9 Copper	GR.10 Aluminium
7-25	7-15	5-10	5-10	10-22	10-25	5-20	30-45	20-50

Taper Shank(Order No. VR303-Dc)

Unit:mm

ORDER NO.	Dc H7	Lc mm	L mm	d mt	Z teeth	CODE NO.
VR303-10.0	10.0	38	168	1	6	6007-430
VR303-11.0	11.0	41	175	1	6	6007-431
VR303-12.0	12.0	44	182	1	6	6007-432
VR303-13.0	13.0	44	182	1	6	6007-433
VR303-14.0	14.0	47	189	1	6	6007-434
VR303-15.0	15.0	50	204	2	6	6007-435
VR303-16.0	16.0	52	210	2	6	6007-436
VR303-17.0	17.0	54	214	2	6	6007-437
VR303-18.0	18.0	56	219	2	6	6007-438
VR303-19.0	19.0	58	223	2	6	6007-439
VR303-20.0	20.0	60	228	2	6	6007-440
VR303-22.0	22.0	64	237	2	6	6007-441
VR303-24.0	24.0	68	268	3	8	6007-442

ORDER NO.	Dc H7	Lc mm	L mm	d mt	Z teeth	CODE NO.
VR303-25.0	25.0	68	268	3	8	6007-443
VR303-26.0	26.0	70	273	3	8	6007-444
VR303-28.0	28.0	71	277	3	8	6007-445
VR303-30.0	30.0	73	281	3	8	6007-446
VR303-32.0	32.0	77	317	4	8	6007-447
VR303-35.0	35.0	78	321	4	8	6007-448
VR303-36.0	36.0	79	325	4	8	6007-449
VR303-38.0	38.0	81	329	4	8	6007-450
VR303-40.0	40.0	81	329	4	8	6007-451